


21.5-inch Touchscreen Monitor

YL-SZPS01Q215TC-V1

ZPS SERIES

PRODUCT VIEWS



Product and connector views from the model specification.

CONSTRUCTION & MOUNTING

Aluminum profiles and metal casing.

Wall mounting; VESA 100 × 100 mm.

EMC SPECIFICATION

Radiated emissions: EN 55032 Class A.
ESD: contact ±4 kV, air ±8 kV; performance criterion B.

DISPLAY

Display size	21.5 inches
Resolution	1920 × 1080
Luminance	500 cd/m ²
Contrast ratio	1000:1
Viewing angle	89 / 89 / 89 / 89°
Display colors	16.7 million
Response time	14 ms
MTBF	30,000 hours

TOUCH

Touch technology	Capacitive touchscreen
Controller / interface	USB; driver-free
Touch response	≤ 5 ms
Surface hardness	Mohs 7

ELECTRICAL

Video inputs	HDMI + VGA
Power input	DC 12 V
Power connector	DC 5521
Operating power	P _{max} < 30 W
Idle power	< 1 W

ENVIRONMENT

Operating temperature	0 to 50°C
Storage temperature	-20 to 60°C
Humidity	10-90% RH

MECHANICAL

VESA mounting	100 × 100 mm
Net weight	TBD



Mechanical & Ordering Details

YL-SZPS01Q215TC-V1

ZPS SERIES

MECHANICAL DRAWING

Overall dimensions and installation details follow the model-specific drawing.

Request the released drawing before defining a panel cutout, mounting clearance or tooling.

ORDERING INFORMATION

Part number	YL-SZPS01Q215TC-V1
Description	21.5-inch capacitive touchscreen monitor; DC 12 V input; HDMI and VGA video inputs.

PACKING LIST

Item	Qty
Touchscreen monitor	1
Power adapter	1
Power cable, 1.8 m	1
HDMI cable, 1.5 m	1

APPLICATION CONSIDERATIONS

Durability and reliability. Select the mechanical design against the specified temperature, humidity and environment.

Electromagnetic interference. Review electrical noise, the EMC specification and the installed system together.

Color performance. Confirm application-specific requirements for clear and accurate visual information.